

SPECIFICATIONS

SR TRANSPORT



SR

REAR ENGINE COACH



Heavy Duty Transport Medium Duty Price

With available seating for up to 40 passengers, big coach curb appeal, and a full complement of big coach style passenger amenities, **CBI** exclusive 35 foot, rear engine design is sure to be a big hit for smaller group transport.

Features include:

- 280 cubic foot pass-through baggage bays
- 20,000 lb. rear axle rating
- ZF independent front suspension with air disc brakes and 60 degree wheel cut
- Pantograph baggage and engine doors
- 05G Carrier compressor
- 295-80R/22.5 Goodyear tires
- Interchangeable windshields
- Spare tire storage behind front bumper
- Bode air operated entrance door

SR Transport- Rear Engine Coach Specification & Features

General

Overall Length (bumpers included)	34.11'
Overall Width	102"
Overall Height	138"
Wheelbase:	228"
Transmission: Allison PTS 3000 Gen IV	
Fuel Capacity:	100 gals
Underfloor Luggage (estimated-w/o lift):	280 cu. ft.
GVWR:	33,000 lbs
Front Axle/ Rating: ZF Independent: 14,600 lbs	
Drive Axle/ Rating: Meritor: 20,000lbs	
Seating:	Amaya Patriot 40 pass w. no bathroom Amaya Patriot 39 pass w/ bathroom

Powertrain

Engine/Cummins ISB 02 275 HP	Standard
Cruise Control/ Fast Idle System	Standard
Block Heater	Standard

Body Construction

Astro Foil Insulation, Sidewalls & Backwall	Standard
Urethane Foam Insulation, Roof	Standard
Rear Energy Absorbing Bumper-White	Standard
FRP Front Bumper	Standard
Underfloor Pass-Through Luggage Compartments	Standard
Pantographic Luggage & Rear Engine Doors	Standard
Remote Control Heated Side Mirrors	Standard
Drip Rails Over Windows & Door	Standard
Fiberglass Exterior Sidewalls, Roof and Fenders	Standard
Exterior White PPG# 904229 w/ blackout window	Standard
Dual Windshield Wiper Motors	Standard
Escape Hatch	Standard
Master Disconnect-Body	Standard
Rear Window	Optional
Custom Paint and Graphics	Optional

Chassis

Brakes-Front: Air Disc/ Rear: Air Drum	Standard
Steel Cage Construction-24" on Center Roof Bows	Standard
SWT Rust Inhibitor Treated Frame Structure	Standard
Stainless Steel Structure Below Floor Line	Standard
Freightliner XBR Coach Chassis	Standard
Rear Axle Ratio 5:13	Standard
Side Mounted Radiator and CAC	Standard
ZF Independent Front Suspension	Standard
w/60 Degree Wheel Cut	Standard
ZF 8018 Steering Box	Standard
ZF Tilt and Telescopic Steering Column	Standard
Front Kneeling Feature	Standard
Neway ADL XB Rear Air Suspension	Standard
Sachs Front and Rear Shocks	Standard
Bendix AD-9 Air Dryer	Standard
Bendix Air Disc Front Brakes	Standard
Meritor Air Drum Rear Brakes	Standard
Wabco Antilock Braking System (ABS)	Standard

Electrical & Lighting

Multiplex-Body Electrical System	Standard
Front and Rear LED Clearance Lights	Standard
Door Activated Stepwell Lights	Standard
Parcel Racks w/ individual reading and air vents	Standard
Interior Lighting LED	Standard
12 volt Electrical & Lighting systems	Standard
270 amp 12 volt Alternator	Standard
8D Batteries	Standard
Battery Disconnect Switch	Standard
Intellitec Multiplex Sealed Module System	Standard
Auxilliary Outlet 12 volt-Driver's area	Standard
Small Back up alarm	Standard

Climate Control

Front Dash Air Conditining	Standard
AC250 Roof Mounted Climate Control systems	Standard
-110,000 BTU (ARI Rating) A/C	
-139,000 BTU Heating	
-24 Volt Closed Circuit System	
-Compressor Carrier 05G	
Floor Heaters	Option
Espar Aux Heat	Standard

Interior

Altro Flooring	Standard
White Standee Line	Standard
National Driver's Seat w/ arm rest	
Match Passenger Seat Fabric	Standard
PA System w/ amplifier and 4 speakers	Standard

Tires & Wheels

295/80 R 22.5" Tires	Standard
Alcoa Dura Bright Wheels (4)	Standard
Spare Tire & Steel Wheel	Standard

Other Equipment

Spare Tire Storage behind Front Bumper	Standard
Rubber Noise Suppression Driver's Area	Standard
T-Slider transit style windows	Standard
Fiberglass Driver Enclosure & Modesty Panel	Standard
Custom molded left Hand Grab Rail	Standard
10 lb Fire Extinguisher	Standard
Reflector Triangles	Standard
LIFT: ADA Package	Option



CHAMPION
BUS, INC.
Thor Industries Commercial Bus Division

331 Graham Rd. Imlay City, MI 48444
Office: 810-724-6474 Fax: 810-724-1844